Grohe Rapid SL Element for WC, 1.13 m installation height

Range: Rapid SL

Description: GROHE Rapid SL installation system – swift to fit with a low-noise flush and

water-saving feature - with flushing cistern GD 2 , 6 I - 9 I, for on-the-wall installations or studded walls, powder coated steel frame, self-supporting, TÜV approved, 2 WC fixing bolts, fixing device for ceramic, WC ceramics with small bearing area (< 205 mm) require , additional accessory 38 779 000, distance of fixing bolts 180/230 mm, outlet bend Ø 90 mm, depth adjustable, reducer Ø 90/110 mm, inlet and outlet connecting set, flushing cistern GD 2, 6

- 9 I, containing following features:, water supply from left/right or back, Insulated against condensation, $\frac{1}{2}$ " water supply connection including integrated , angle valve and push fit flexible hose union, for on-the-wall installation please order wall brackets 38 558 00M (sold separately), for mounting of small flush plates please order , revision shaft 40 911 000 (sold

separately)

 Product Code:
 G-38528001

 ERP Code:
 G-38528001

 Barcode:
 4005176863943

 Product
 10 Year Warranty

Features: Dimensions:


(l) 1170mm x (w) 520mm x (h) 150mm

Package Weight: 12.06
CAD3D: Download



Product Images





MOT



10 Year Warranty